



SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

GE5010

Section 1. Product and company identification

Product name : GE5010

Manufacturer/Importer/ : Momentive Performance Materials LLC

Distributor Information 260 Hudson River Road

Waterford NY 12188

Contact person : 4information@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC

1-800-424-9300

Section 2. Hazards identification

Classification of the substance or

mixture

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 1B TOXIC TO REPRODUCTION - Category 1B

GHS label elements

Hazard pictograms

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.H317 May cause an allergic skin reaction.

H360F May damage fertility. H360 May damage the unborn child.

Precautionary statements

General : Not applicable.

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Use personal protective equipment as required.

Wear protective gloves. Wear eye or face protection.

GE5010 Page:2/12

Avoid breathing dust.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the

workplace.

Response : IF exposed or concerned:

Get medical attention.

IF ON SKIN:

Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs:

Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Storage : Store locked up.

Disposal : P501Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result in classification

Uncured product is irritating to eyes, skin, and respiratory system.
 Generates methanol during cure. Generates ammonia during cure.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Chemical name : Not available

Hazardous ingredients	% by weight	
		number
Distillates (petroleum), hydrotreated middle	5 - 10	64742-46-7
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-	1 - 5	999-97-3
Tin, dibutylbis(2,4-pentanedionatokappa.O2,.kappa.O4)-,	0.1 - 1	22673-19-4
(OC-6-11)-		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

GE5010 Page: 3/12

as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove

victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first aid personnel : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).

: water jet

Specific hazards arising from the chemical

: No specific fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are

formed due to oxidative degradation.

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to

keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to

any waterway, sewer or drain.

Special protective equipment for : Fire-fighters should wear appropriate protective equipment and self-

GE5010 Page:4/12

fire-fighters

contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal w

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways,

soil or air).

Methods and material for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste

disposal.

Large spill : Move containers from spill area. Approach release from upwind.

Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact

information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see section 8 of

SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a

compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also

Section 8 for additional information on hygiene measures.

Conditions for safe storage, : Store in accordance with local regulations. Store in original

GE5010 Page: 5/12

including any incompatibilities

container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product

Respiratory protection

: Use a properly fitted, particulate filter respirator complying with an

GE5010 Page:6/12

approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Solid Color : White

Odor : ammonia
Odor threshold : Not available
pH : Not applicable.

Melting point: Not availableBoiling point: Not available

Flash point : > 94 °C (201.20 °F) (Estimated.) Product does not flash below

93.3C (200F) during test; no actual flash point >93.3 C was

determined.

Burning time: Not availableBurning rate: Not availableEvaporation rate: Not availableFlammability (solid, gas): Not available

Lower and upper explosive : Lower: Not available (flammable) limits : Upper: Not available

Vapor pressure : Not applicable.

Vapor density : Not available

Relative density : 1.02

Solubility : PARTIAL IN TOLUENE

Solubility in water : Insoluble

Partition coefficient: n- Not available

octanol/water

Auto-ignition temperature: Not availableDecomposition temperature: Not availableSADT: Not available

Viscosity : Dynamic: Not available

Kinematic: Not available

Volatile organic content : 2.2 % (w/w)

27 g/l

Other information

No additional information

Section 10. Stability and reactivity

GE5010 Page: 7/12

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions

will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition : Under normal conditions of storage and use, hazardous

products decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Conclusion/Summary : Not determined

Irritation/Corrosion

Conclusion/Summary

Skin:Not determinedeyes:Not determinedRespiratory:Not determined

Sensitization

Conclusion/Summary

Skin : Not determined
Respiratory : Not determined

Mutagenicity

Conclusion/Summary : Not determined

Carcinogenicity

Conclusion/Summary : Not determined

Reproductive toxicity

Conclusion/Summary : Not determined

Teratogenicity

Conclusion/Summary : Not determined

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Tin, dibutylbis(2,4-	Category 1		thymus
pentanedionato-			
.kappa.O2,.kappa.O4)-, (OC-6-			
11)-			

GE5010 Page:8/12

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Tin, dibutylbis(2,4-	Category 1		thymus
pentanedionato-			
.kappa.O2,.kappa.O4)-, (OC-6-			
11)-			

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated middle	ASPIRATION HAZARD - Category 1ASPIRATION
	HAZARD - Category 1ASPIRATION HAZARD -
	Category 1

Information on the likely routes of : Not available

exposure

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Irritating to mouth, throat and stomach. **Ingestion**

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following: Eye contact

pain or irritation

watering redness

Inhalation Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact Adverse symptoms may include the following:

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Not available **Potential immediate effects** Not available Potential delayed effects

Long term exposure

Not available **Potential immediate effects** Not available Potential delayed effects

Potential chronic health effects

Conclusion/Summary Not determined

GE5010 Page:9/12

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: May damage the unborn child.

Developmental effects: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	18,996.2 mg/kg
Route	ATE value
Dermal	11,397.7 mg/kg
Route	ATE value
Inhalation (vapors)	417.9 mg/l

Section 12. Ecological information

Ecotoxicity

Conclusion/Summary : Not available

Persistence/degradability

Conclusion/Summary : Not available

Bioaccumulative potential

Product/ingredient name	Species	Exposure	LogPow	BCF	Potential
Silanamine, 1,1,1-trimethyl-N-			1.19	-	low
(trimethylsilyl)-					

Mobility in soil

Soil/water partition coefficient

: Not available

(KOC)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental

GE5010 Page: 10/12

protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. See Section 8 for information on appropriate personal protective equipment.

Section 14. Transport information

Special precautions for user

: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. Regulatory information

United States

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None required.

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

California Prop. 65:

WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada

WHMIS (Canada)

Class D-2A: Material causing other toxic effects (Very toxic).

International regulations

International lists

Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. **Philippines inventory (PICCS):** All components are listed or exempted.

GE5010 Page:11/12

United States inventory (TSCA 8b): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

Label requirements

: Causes serious eye irritation. CAUSES SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED.

Hazardous Material Information System III (U.S.A.):

induit tous tratterial information system in (Cishi)		
Health		2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

statements

Not applicable.

History

Date of printing: 12/17/2015Date of issue/Date of revision: 08/03/2015Date of previous issue: 04/10/2015

Version : 1.3

Prepared by

Key to abbreviations

: Product Safety Stewardship

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MÄRPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : Not available

Notice to reader

Unless otherwise specified in section 1, Momentive Products are intended for industrial application only. They are not intended for specific medical applications, neither for long-lasting (> 30 days) implantation into the human body, injected or directly ingested, nor for the manufacture of multiple usable contraceptives Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GE5010 Page: 12/12

®,*, and TM indicate trademarks owned by or licensed to Momentive.