

ASHLAND

SAFETY DATA SHEET

Page: 1

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name Valvoline™ 4T STROKE FULL SYNTHETIC SAE 10W40
MOTORCYCLE OIL

Product code 507679

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

ASHLAND[®]

SAFETY DATA SHEET

Page: 2

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	>=80-<90%
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	>=5-<10%
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=1.5-<5%

ASHLAND[®]

SAFETY DATA SHEET

Page: 3

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

ASHLAND[®]

SAFETY DATA SHEET

Page: 4

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons, Aldehydes, boron oxides, nitrogen oxides (NO_x)

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

ASHLAND®

SAFETY DATA SHEET

Page: 5

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC		64742-65-0	
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,000 mg/m ³	
NIOSH	Recommended exposure limit (REL):	5 mg/m ³	Mist.
NIOSH	Short term exposure limit	10 mg/m ³	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m ³	Mist.
ACGIH	time weighted average	5 mg/m ³	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation

ASHLAND®

SAFETY DATA SHEET

Page: 6

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.
Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Boiling point/boiling range	(Estimated)662 °F / 350 °C
Flash point	> 390 °F / > 199 °C Cleveland open cup
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	0.133 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Density	0.862 g/cm3
Viscosity, kinematic	(+/- 0.5)14.5 mm2/s @ 100 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

None known.

Incompatible products

Oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, Aldehydes

Hazardous reactions

Product will not undergo hazardous polymerization.

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity - : no data available
Product

Acute oral toxicity - Components

HYDROTREATED : LD 50: > 15 g/kg Species: Rat
HEAVY PARAFFINIC
BASE OIL

DISTILLATES : LD 50: > 5,000 mg/kg Species: Rat
(PETROLEUM),
SOLVENT-DEWAXED
HEAVY PARAFFINIC

HEAVY PARAFFINIC : LD 50: > 15 g/kg Species: Rat
DISTILLATE

Acute inhalation toxicity

Acute inhalation toxicity - : no data available
Product

Acute dermal toxicity

Acute dermal toxicity - : no data available
Product

Acute dermal toxicity - Components

HYDROTREATED : LD 50: > 5 g/kg Species: Rabbit
HEAVY PARAFFINIC
BASE OIL

DISTILLATES : LD 50: > 5,000 mg/kg Species: Rabbit
(PETROLEUM),
SOLVENT-DEWAXED
HEAVY PARAFFINIC

HEAVY PARAFFINIC : LD 50: > 5 g/kg Species: Rabbit
DISTILLATE

ASHLAND®

SAFETY DATA SHEET

Page: 8

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

Revision Date: 11/15/2012
Print Date: 2/20/2014
MSDS Number: R0412112
Version: 1.6

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects

Toxicity to fish

Toxicity to fish - Product : no data available

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other aquatic invertebrates - Product : no data available

Toxicity to algae

Toxicity to algae - Product : no data available

Toxicity to bacteria

Toxicity to bacteria - Product : no data available

ASHLAND

SAFETY DATA SHEET

Page: 9

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

ASHLAND[®]

SAFETY DATA SHEET

Page: 10

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

SARA 311/312 Classification

No SARA Hazards

SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

New Jersey RTK Label Information

HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0
HEAVY PARAFFINIC DISTILLATE	64742-54-7
POLYOLEFIN AMIDE ALKENEAMINE	
LUBRICANT ADDITIVE	

Pennsylvania RTK Label Information

HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0

ASHLAND®

SAFETY DATA SHEET

Page: 11

Revision Date: 11/15/2012

Print Date: 2/20/2014

MSDS Number: R0412112

Version: 1.6

Valvoline™ 4T STROKE FULL SYNTHETIC
SAE 10W40 MOTORCYCLE OIL
507679

HEAVY PARAFFINIC DISTILLATE	64742-54-7
-----------------------------	------------

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	q (quantity restricted)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

