		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : NAPA® MAC'S SILICONE SPRAY  
SILICONE SPRAY

### Recommended use of the chemical and restrictions on use



<b>Details of the supplier of the safety data sheet</b> Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	<b>Emergency telephone number</b> CHEMTREC DIRECT 1-800-424-9300  <b>Product Information</b> 1-844-696-4836
--	---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable aerosols : Category 1  
Eye irritation : Category 2A  
Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)


### GHS Label element

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : Extremely flammable aerosol.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
Keep away from heat/sparks/open flames/hot surfaces. - No

		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection/ face protection.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Flam. Liq. 2; H225 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	51.17

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

 NAPA® MAC'S SILICONE SPRAY SILICONE  
 SPRAY


Version: 1.1

833347

ACETONE	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	41.86
CARBON DIOXIDE	124-38-9	Press. Gas Liquefied gas; H280	4.20
n-HEPTANE	142-82-5	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304	2.04

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
 If unconscious place in recovery position and seek medical advice.  
 Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
 If on skin, rinse well with water.  
 Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
 stomach or intestinal upset (nausea, vomiting, diarrhea)  
 irritation (nose, throat, airways)  
 loss of appetite  
 irregular heartbeat  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.

Notes to physician : No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES


Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Alcohol-resistant foam  
 Carbon dioxide (CO2)  
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Aldehydes  
 carbon dioxide and carbon monoxide  
 organic compounds  
 formaldehyde  
 Hydrocarbons  
 silicon oxides

Specific extinguishing :

		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY  833347		Version: 1.1

methods

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

---

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.  
Container may be opened only under exhaust ventilation

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY

Version: 1.1

833347

hood.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 No smoking.  
 Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	TWA	500 ppm	OSHA_TRANS
		TWA	300 ppm	ACGIH
		TWA	2,000 mg/m3	OSHA_TRANS
ACETONE	67-64-1	TWA	1,370 mg/m3	ACGIH
		TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		REL	250 ppm 590 mg/m3	NIOSH/GUIDE
		PEL	1,000 ppm 2,400 mg/m3	OSHA_TRANS
		TWA	250 ppm	ACGIHLIS_P
CARBON DIOXIDE	124-38-9	STEL	500 ppm	ACGIHLIS_P
		TWA	750 ppm 1,800 mg/m3	Z1A
		STEL	1,000 ppm 2,400 mg/m3	Z1A
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		REL	5,000 ppm 9,000 mg/m3	NIOSH/GUIDE
		STEL	30,000 ppm 54,000 mg/m3	NIOSH/GUIDE
		PEL	5,000 ppm	OSHA_TRA

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

 NAPA® MAC'S SILICONE SPRAY SILICONE  
 SPRAY

Version: 1.1

833347

			9,000 mg/m3	NS
n-HEPTANE	142-82-5	REL	85 ppm 350 mg/m3	NIOSH/GUID E
		Ceil_Time	440 ppm 1,800 mg/m3	NIOSH/GUID E
		PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ACETONE	67-64-1	acetone	Urine	Sampling time: End of shift.	50 mg/l	
Remarks:	Nonspecific					

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
 In the case of dust or aerosol formation use respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection  
 Material : nitrile rubber

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:  
 impervious clothing  
 Safety shoes

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

Version: 1.1

NAPA® MAC'S SILICONE SPRAY SILICONE  
SPRAY

833347

Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : aerosol
- Physical state : aerosol
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 133 °F / 56 °C  
(1,013.333333 hPa)  
Calculated Phase Transition Liquid/Gas Value for Component
- Flash point : -4 °F / -20 °C  
Calculated Flash Point Value for Component
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 12.8 %(V)  
GLP: Calculated Explosive Limit
- Lower explosion limit : 2.6 %(V)  
GLP: Calculated Explosive Limit
- Vapour pressure : 308 hPa (25 °C)  
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : No data available
- Density : 1.078 g/cm<sup>3</sup> (25 °C)
- Solubility(ies)  
Water solubility : No data available



**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

NAPA® MAC'S SILICONE SPRAY SILICONE  
SPRAY

Version: 1.1

833347

- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Thermal decomposition : No data available
- Viscosity
  - Viscosity, dynamic : No data available
  - Viscosity, kinematic : Not applicable
- Oxidizing properties : No data available

---


**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.
- Possibility of hazardous reactions : Vapours may form explosive mixture with air.
- Conditions to avoid : Heat, flames and sparks.
- Incompatible materials : Acids  
alkalis  
Amines  
Ammonia  
halogens  
peroxides  
Reducing agents  
Strong oxidizing agents
- Hazardous decomposition products
  - Aldehydes
  - carbon dioxide and carbon monoxide
  - formaldehyde
  - Hydrocarbons
  - organic compounds
  - silicon oxides

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Information on likely routes of exposure : Inhalation  
Skin contact

		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Acute oral toxicity : LD 50 (Rat): > 8,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 3400 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rat): > 4,000 mg/kg

**ACETONE:**

Acute oral toxicity : LD 50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat, female): 76 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): > 7,426 mg/kg

**n-HEPTANE:**

Acute oral toxicity : LD 50 (Rat): Expected > 5,000 mg/kg  
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 29.29 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): Expected > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: Information given is based on data obtained from similar substances.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**


Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Mildly irritating to skin

		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

**ACETONE:**

Result: Mildly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

**CARBON DIOXIDE:**

Result: Not irritating to skin

**n-HEPTANE:**

Result: Irritating to skin

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Mildly irritating to eyes

**ACETONE:**

Result: Irritating to eyes

**CARBON DIOXIDE:**

Result: Not irritating to eyes

**n-HEPTANE:**

Result: Mildly irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:**

n-HEPTANE:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

**Germ cell mutagenicity**


Not classified based on available information.

**Components:**

n-HEPTANE:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
 Test species: rat hepatocytes  
 Method: OECD Test Guideline 473  
 Result: negative

: Test Type: Ames test  
 Method: OECD Test Guideline 471  
 Result: negative

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY  833347		Version: 1.1

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:**

ACETONE:

Exposure routes: Inhalation

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

n-HEPTANE:

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

May be fatal if swallowed and enters airways.

ACETONE:

May be harmful if swallowed and enters airways.

n-HEPTANE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

 NAPA® MAC'S SILICONE SPRAY SILICONE  
 SPRAY

Version: 1.1

833347

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**ACETONE:**

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 4,740 - 6,330 mg/l  
 Exposure time: 96 h  
 Test Type: static test

LC 50 (Fathead minnow (Pimephales promelas)): 8,733 - 9,482 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

Toxicity to algae : NOEC (Microcystis aeruginosa): 530 mg/l  
 Exposure time: 8 d  
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2,112 mg/l  
 Exposure time: 28 d  
 Test Type: flow-through test

**n-HEPTANE:**

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 1.5 mg/l  
 Exposure time: 48 h  
 Test Type: static test

LC 50 (Mysidopsis bahia (opossum shrimp)): 0.1 mg/l  
 Exposure time: 96 h  
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Water flea (Daphnia magna)): 1 mg/l  
 Exposure time: 21 d  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211  
 Remarks: Information given is based on data obtained from similar substances.


**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability**
**ACETONE:**

Biodegradability : Result: Readily biodegradable  
 Biodegradation: 90.9 %

		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY  833347		Version: 1.1

Exposure time: 28 d  
 Method: OECD Test Guideline 301B

n-HEPTANE:  
 Biodegradability : Result: Readily biodegradable

**Bioaccumulative potential**

ACETONE:  
 Partition coefficient: n-octanol/water : log Pow: -0.24

n-HEPTANE:  
 Partition coefficient: n-octanol/water : log Pow: 4.66

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.  
  
 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations  
 REGULATION**

**SAFETY DATA SHEET**

Revision Date: 07/31/2015

Print Date: 9/29/2015

SDS Number: R0254499

NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY

Version: 1.1

833347

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

UN 1950	Aerosols	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**U.S. DOT - RAIL**

UN 1950	Aerosols	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**U.S. DOT - INLAND WATERWAYS**

UN 1950	Aerosols	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**TRANSPORT CANADA - ROAD**

UN 1950	AEROSOLS	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**TRANSPORT CANADA - RAIL**

UN 1950	AEROSOLS	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**TRANSPORT CANADA - INLAND WATERWAYS**

UN 1950	AEROSOLS	2.1			LIMITED QUANTITY
---------	----------	-----	--	--	------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**


UN 1950	AEROSOLS	2.1			MARINE POLLUTANT:(ALIPHATIC PETROLEUM NAPHTHA)LIMITED QUANTITY
---------	----------	-----	--	--	--

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

UN 1950	Aerosols, flammable	2.1			
---------	---------------------	-----	--	--	--

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

UN 1950	Aerosols, flammable	2.1			
---------	---------------------	-----	--	--	--

		Page: 16
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

UN	1950	AEROSOLS	2

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ACETONE	67-64-1	5000	11944.177691

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard

**SARA 313 Component(s)SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


**Pennsylvania Right To Know**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	50.00 - 70.00 %
ACETONE	67-64-1	30.00 - 50.00 %
CARBON DIOXIDE	124-38-9	1.00 - 5.00 %
n-HEPTANE	142-82-5	1.00 - 5.00 %

**New Jersey Right To Know**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	50.00 - 70.00 %
ACETONE	67-64-1	30.00 - 50.00 %
CARBON DIOXIDE	124-38-9	1.00 - 5.00 %



		Page: 17
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

DIMETHYL SILICONES AND SILOXANES	63148-62-9	1.00 - 5.00 %
n-HEPTANE	142-82-5	1.00 - 5.00 %

**California Prop 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.

BENZENE 71-43-2

ETHYL BENZENE 100-41-4

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

TOLUENE 108-88-3

BENZENE 71-43-2

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIOC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

<b>NiTEO</b> PRODUCTS		Page: 18
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 07/31/2015

<b>NFPA:</b>	<b>HMS III:</b>						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>2</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>3</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>3</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>3</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

### NFPA Flammable and Combustible Liquids Classification

Not applicable

### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H305	May be harmful if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet


Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

		Page: 19
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2015
		Print Date: 9/29/2015
		SDS Number: R0254499
NAPA® MAC'S SILICONE SPRAY SILICONE SPRAY		Version: 1.1
833347		

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
**WHMIS : Workplace Hazardous Materials Information System**