

1. Identification

Product identifier Acry-Lac Super Cleaner/Release Agent

Other means of identification

Product code RS-600-V

Recommended use Pre-Cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Medallion Refinish System

Address 5751 N. Webster Street
 Dayton, OH 45414
 United States

Telephone TECH SUPPORT 937-890-6547
 SALES 937-890-6547
 PHONE 800-257-6547

Website www.medallionrefinish.com

E-mail info@rubber-seal.net

Contact person Elizabeth Wells

Emergency phone number MAIN OFFICE: M-F 800-257-6547
 7:45am-4:30pm
 EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Acute toxicity, dermal Category 4
 Acute toxicity, inhalation Category 4
 Skin corrosion/irritation Category 2
 Serious eye damage/eye irritation Category 2A
 Carcinogenicity Category 2
 Reproductive toxicity (the unborn child) Category 2
 Specific target organ toxicity, repeated exposure Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
 Hazardous to the aquatic environment, long-term hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Heptane Regulatory (CAS 142-82-5)	TWA	435 mg/m3 100 ppm
	Ceiling	1800 mg/m3
	TWA	440 ppm 350 mg/m3
Toluene (CAS 108-88-3)	STEL	85 ppm 560 mg/m3
	TWA	150 ppm 375 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Colorless

Odor Solvent.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
Heptane Regulatory (CAS 142-82-5)		
<u>Acute</u>		
Inhalation		
LC50	Rat	103 mg/l, 4 Hours
LD50	Mouse	75 mg/l, 2 Hours
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound (Heptane, Xylene Mixed Isomers)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA), List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA), List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)
Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Ethylbenzene (CAS 100-41-4)

Heptane Regulatory (CAS 142-82-5)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Ethylbenzene (CAS 100-41-4)

Heptane Regulatory (CAS 142-82-5)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylbenzene (CAS 100-41-4)

Heptane Regulatory (CAS 142-82-5)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No